MAXHUB



MAXHUB V5 Classic Series

Legend Retold



4K UHD Display

Low Parallax | Anti-glare 90% NTSC Wide Colour Gamut

12MP Camera

Auto Framing | Higher SNR

Smart Writing

High-precision IR Touch Technology

Seam Speakers

2.1 Stereo Sound 40W High-power Speaker

Multiple Sizes

55/65/75/86 inches Available

3 Display Modes

Presentation | Standard | Night Mode

- > Seam Speakers, Creative Acoustic Structure
- > 12MP Camera: Enhanced A&V Capacity
- > High-precision IR Touch System
- > Vivid Display: Presentations Come to Live
- > Voice Localisation via 6-element Mic Array



> MAXHUB V5 Classic Series

Legend Retold

Product Specification Classic Series

Display	C55FA	C65FA	C75FA	C86FA
Size	55 inch	65 inch	75 inch	86 inch
Ratio	16:9	16:9	16:9	16:9
Resolution	3840×2160	3840×2160	3840×2160	3840×2160
Contrast Ratio	4500:1	4000:1	4000:1	4000:1
/iewing Angle	178° (H/V)	178° (H/V)	178° (H/V)	178° (H/V)
Colour Gamut	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Backlight Structure	DLED	DLED	DLED	DLED
Lifespan	≥30,000 hours	≥30,000 hours	≥30,000 hours	≥30,000 hours
Touch System				
Fouch Principle	Infrared	Infrared	Infrared	Infrared
Touch Points	20 Points	20 Points	20 Points	20 Points
	Windows 10/Windows 8/	Windows 10/Windows 8/	Windows 10/Windows 8/	Windows 10/Windows 8/
Supported Systems	Windows 7/Windows XP/	Windows 7/Windows XP/	Windows 7/Windows XP/	Windows 7/Windows XP/
	Android/Linux/macOS X/Chrome	Android/Linux/macOS X/Chrome	Android/Linux/macOS X/Chrome	Android/Linux/macOS X/Chrome
Minimum Recognisable Object	2mm	2mm	2mm	2mm
Fouch Object	Finger, Stylus	Finger, Stylus	Finger, Stylus	Finger, Stylus
Fouch Accuracy	±1mm	±1mm	±1mm	±1mm
Vriting Height	≤2mm	≤2mm	≤2mm	≤2mm
Fouch Resolution	32768(W)×32768(D)	32768(W)×32768(D)	32768(W)×32768(D)	32768(W)×32768(D)
Speakers				
Channel	2.1	2.1	2.1	2.1
Power	2×10W+20W	2×10W+20W	2×10W+20W	2×10W+20W
Microphone	2×10₩120₩	2×10₩120₩	2×10₩120₩	2×10₩120₩
•	6	6	6	6
Quantity				
Voice Pickup Range	Up to 8m	Up to 8m	Up to 8m	Up to 8m
Camera				
Quantity	1	1	1	1
Pixels	12MP	12MP	12MP	12MP
Location	In the Middle of the Upper Bezel			
I/O Ports				
HDMI IN	1	1	1	1
JSB 2.0	1	1	1	1
JSB 3.0	2	2	2	2
USB Type-C	2	2	2	2
rouch	1	1	1	1
AUDIO OUT	1	1	1	1
RS232	1	1	1	1
Compatible Modules*				
PC Module	MT51 (Windows 10)	MT51 (Windows 10)	MT51 (Windows 10)	MT51 (Windows 10)
Android Module	SA08 (Android 9.0)	SA08 (Android 9.0)	SA08 (Android 9.0)	SA08 (Android 9.0)
Accessories				
Power Cable	×1	×1	×1	×1
Stylus	×2	×2	×2	×2
Wall Mount	×1	×1	×1	×1
Ni-Fi Module	×1	×1	×1	×1
Environment				
	0°C to 40°C	0°C tc 40°C	0°C to 40°C	0°C +- 40°C
Operation Temperature		0°C to 40°C 10% to 90%RH	10% to 90%RH	0°C to 40°C
Operation Humidity	10% to 90%RH			10% to 90%RH
Storage Temperature	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Storage Humidity	10% to 90%RH	10% to 90%RH	10% to 90%RH	10% to 90%RH